



Installation Instructions

Ducktail Mazda MX-5 NA

Date:	13.12.2021	Revision:	0
Editor:	Nico Hafner	Vehicle:	Mazda MX-5 NA

Scope of delivery:

- Ducktail Spoiler passend für MX-5 NA



Warning:

Please read this instruction before installation and get in touch with the work on the car! Ideally, have the installation done by a professional workshop. Tighten all screws with the torque recommend by the manufacturer. The assembling company is liable for installation mistakes. In case of manufacturing defects, the corresponding components will be replaced without any costs within the warranty period.

Nico Hafner	gez. Nico Hafner
Name of editor	Signature

SPS Motorsport GmbH
Im Petersfeld 4
65624 Altendiez

Telefon: 06432/6409960
Fax: 06432/6409966
Web: <http://sps-motorsport.com>
E-Mail: info@sps-motorsport.com



Preparation:

- Park the vehicle, switch off the engine and let the engine cool down
- Clean the trunk

Installation of the ducktail:

- Place the ducktail on the trunk of the car and align it in the middle. If available, you can use the third brake light as an orientation
- Drill holes in the middle of the countersinks in the ducktail and transfer them to the trunk
- Remove the ducktail from the trunk
- Seal the drills in the trunk using a paint pen
- Install rivet nuts in M6 in the holes of the trunk
- Install and tighten the ducktail using M6 screws for all rivet nuts

Final work on the vehicle:

- Control, if every screw is tightened correctly

Nico Hafner	gez. Nico Hafner
Name of editor	Signature